

# VJTI

### Veermata Jijabai Technological Institute

(Central Technological Institute, Maharashtra State, INDIA) H. R. Mahajani Marg, Matunga, Mumbai 400019

Tel.No. +91 22 24198101-02 Fax: +91 22 24102874

www.vjti.ac.in

Ref No. STR/Maintenance/ 79 \ /2025

Date:- 22/05/2025 2 2 MAY 2025

# **QUOTATION NOTICE**

M/s.	• •			•		÷	٠	•	٠	٠	•	•			•	8.5	•	٠	٠	٠	٠	٠	٠	•		×	•	•	•	•
51000141018	HERE!	275	327	277	1960	135	200	:87	522		=	323	SA	(6)	8															

Subject:- Providing and fixing profiled sheet roofing over the open terrace of the Mechanical Engineering Department at VJTI.

Enquiry Issue Date: 10/05/2025 Last date of Submission: Immediate

Estimated Cost: Rs. 9,16,776.30/- (Including GST)

Dear Sir,

The Institute intends to undertake Providing and fixing profiled sheet roofing over the open terrace of the Mechanical Engineering Department at VJTI for which sealed quotation are invited. You are requested to quote the rates/pripce/cost in Annexure – I.

#### **TERMS & CONDITIONS**

#### 1. Quotation submission

- Sealed quotation, addressed to Director, VJTI; shall be posted or submitted at First Floor, Inward Section, VJTI, H. R. Mahajani Marg, Matunga, Mumbai 400019, in person so as to reach this Office on or before the due date and time.
- The sealed envelope shall be superscripted with Reference No. mentioned overleaf.
- Quotation must be printed on the letterhead of the firm/vendor/company/organization otherwise quotation shall be rejected outright.
- Please mention your GST, PAN and any other relevant identification /registration numbers.
- If the due date turns out to be a holiday for unforeseen reason, quotation should be accepted on the next working day.
- The quotation should be valid for a period of 60 days.
- The rate/price/cost quoted should be inclusive of all items, labour charges, transportation cost etc.

#### 2. Payment:-

- Payment after the satisfactory completion of work will be made by bank transfer only.
- As per Institute policy, no advance payment will be made.

## 3. Acceptance of quotation

- Institute reserves the right of rejection of any or all the quotations without assigning any reasons.
- Canvassing in any form would lead to rejection of quotations.
- Quotations received after the due date will not be considered.
- Quotations without Signature and Stamp / Seal are likely to be rejected.
- Terms other than this may be specified separately.



# 4. Additional Terms & Conditions:-

- 1. The contractor should have experience in completion of similar type of work costing minimum 80% of estimated cost of the work during the last three years.
- 2. Site visit by the Bidder to understand the scope of work is compulsory for submission of quotation.
- 3. The experienced/qualified Supervisor (Diploma / Degree Civil Engineer) should be present at the worksite when work is in progress.
- 4. All the debris generated from the works is to be removed by the Contractor. It should be disposed of away from the Institute premises following Municipality rules.
- 5. The work may be carried out on all days from 8.00 AM to 6.00 PM. For working in late hour's Dean (I & M) permission shall be obtained.
- 6. Successful bidder shall submit bar chart for the execution of work.
- 7. Duration: 60 days. Works should be completed within 30 calendar days from the date of work order.
- 8. An incentives of Rs.5,000/- per day will be given if work is completed early. A penalty of Rs.10,000/- per day will be levied if work is delayed.
- 9. Variation of +/- 25% in contract cost (Excess Qty/ Extra items) permitted with approval of Dean (I & M), subject to maximum contract cost of Rs.10 Lakhs.
- 10. Variation in contract cost (Excess Qty / Extra items) beyond 25% will be approved by Director.

Dean (I & M)

2215128

# Annexure – I ( Proforma for submission of price quote) Details Specification are as follows:- Providing and fixing profiled sheet roofing over the open terrace of the Mechanical Engineering Department at VJTI.

Sr.	1 Accountion	1			
No. 1.		Qty	Unit	Rate	Amount
1.	Dismantling brick masonry in lime or cement mortar and stacking the materile as directed with all leads, lifts etc.	2.88	Cu.M		
	as directed with all leads, lifts etc.	2.00	Cu.IVI		
2.	Providing and laying Cast in situ/Ready Mix cement concrete in M20 of trap/ granite/quartzite/gneigs motel for the concrete in				
	M20 of trap/ granite/quartzite/gneiss metal for plain or molded sills,	2.88	Cu.M		
	including steel centering, formwork, laying/pumping, compacting, roughening them if special finish is laying/pumping, compacting,				
	plaster is considered for rendering upeyon and by	1			
	Newly laid concrete shall be covered by gunny bag, plastic, tarpaulin etc.				
3.	- The section of the				
	Providing internal cement plaster 25 mm thick in single coat using Ready to use wall plaster in cement mortar 1:5 to concrete, brick, stone surfaces in all positions including scaffolding and arrived the standard of the st	19.20	Sq.M		
			•		
	and conclude members complete With Drion Ammount Co				
1					
4.	Providing and erecting structural steel for sakav with all bracing gusset plates	0.30	M.T		
		0.50	141.1		
	fabricating, hoisting, erecting, fixing in position, making riveted/ bolted/welded connection and oil painting with 2 coats of approved quality				
	chade etc. complete. Commen		*		
5.	Providing structural steel work in hollow section of	2760			
4.0	mis office in Square, recivilitiar and round chops from 25	2.760	M.T		
1.0	section as per 15 4925 1 ST STUCTE ade produced from the	1			
1	arriage route etc. as per detailed designs and drawing on as distant				
j	including cutting, fabricating, hoisting, erecting, fixing in position, making riveted/bolted/ welded connections and painting complete.				
U I	Troviding And fixing Chemical anchor holt	52.0			
7	Providing and fixing colour coated Zincalume (R) AZ150 (min 150	52.0 151.67	Nos		
1 8	smo/sq.mt. total on each side) profiled sheets for roofing. The feed	131.07	Sq.M		
- 1	is manufactured out of nominal 0.45 mm Base Metal Thistman (DMT) (0.5				
0	mm TCT), Hi-strength steel with min.550 MPa yield strength, metallic hot dip coated with Aluminium-Zinc alloy (55% aluminium 43.4% zinc 1.6% with COLORDOND (P.)				
S	silicon) with COLORBOND (R) steel quality super durable polyester paint				
	with morganic pigment). The paint shall have a total agating				
l.	mekness of nominal 35 um, comprising of nominal 25 um exterior cost on				
L	op surface and nominal 10 um reverse coat on back surface. Profile sheet				
d	shall have nom. 950-1050 mm effective cover width and nominal 25-30 mm				
c	deep ribs with subtle square fluting in the five pan at nominal 180-250 mm center- to-center. The end rib shall be designed for anti-capillary groove.				
a	and return leg. The feed material should have coil manufacturers product				
a	letails marked a regular interval. Including fasteners with min, fastened with				
n	nin. 25 um Zinc-Tin alloy coated, Hex head, self-drilling screw etc.				
c	omplete. (weight of profile 4.52 Kilogram/ One Square Metre)				



8	Providing and fixing valley gutter of 22 B.W.G. (0.8 mm) plain galvanised iron sheets 120 cm wide with teak wood planking 20 mm thick including two coats of coal-tarring the upper surface of plank etc. complete.  Removal of debrie including the complete including the complete including the complete including the complete.	26.88	Rmt	
0	Removal of debris including loading and unloading on approved dumping ground by truck for the lead of 50 kilometers.etc complete.  Providing and fixing PVC Rain water.	5.88	Cu.m.	
1	Providing and fixing P.V.C. Rain water pipes of 110mm outer diameter and having wall thickness of 2.2 to 2.7 mm confirming to I.S. 13592-1992 including proper rainwater receiving recess with P.V.C. plug, bend, necessary fittings, such as, offsets, shoes, inluding fixing the pipe on wall using approved wooden cleats projecting 25mm to 40mm from face of wall a fixing with clips of approved quality and One Number, filing the joint using rubber gasket with solvent cement and properly resting the shoe of pipes on C.C. or masonry blocks, including necessary scaffolding and maintenance for 3 yrs for any leakages or dislocations of pipes. All the P.V.C. fittings and additional 2 piece socket clips shall be got approved from engineer in charge etc. completee.  Providing and applying two coats of lead/zinc base oil paint/ bituminious paint of approved colour to new structural steel.	20.00	Rmt	
	paint of approved colour to new structural steel work and iron work in buildings including scaffolding if necessary, cleaning and preparing the course for providing Optimum design of truss, box sections, Built up	150.00	Sq.M	
1	Basic Amount:-			
1	CGST 9%			
	GGST 9%			

Dean (I & M)